



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/815,760	04/02/2004	Michiko Endo	1614.1168C	9967

21171 7590 10/25/2006

STAAS & HALSEY LLP
SUITE 700
1201 NEW YORK AVENUE, N.W.
WASHINGTON, DC 20005

EXAMINER

DHARIA, PRABODH M

ART UNIT

PAPER NUMBER

2629

DATE MAILED: 10/25/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

**UNITED STATES DEPARTMENT OF COMMERCE****U.S. Patent and Trademark Office**

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

APPLICATION NO./ CONTROL NO.	FILING DATE	FIRST NAMED INVENTOR / PATENT IN REEXAMINATION	ATTORNEY DOCKET NO.
---------------------------------	-------------	---	---------------------

10815,760

10-24-06

Michiko ENDO

1614.1168C

EXAMINER

PRABODH DHARIA

ART UNIT

PAPER

2629

20061024

DATE MAILED:

Please find below and/or attached an Office communication concerning this application or proceeding.

Commissioner for Patents

Receipt is acknowledged of papers submitted on 10-10-2006 under IDS, which have been placed of record in the file. The IDS has been searched and considered for teaching of allowed claimed limitations. However, after thorough search and consideration IDS failed to recite or disclosed following allowed claim limitations:

A coordinate input apparatus for designating a particular set of coordinate in three-dimensional space, comprising: a cylindrical magnet having a center axis; an annular magnet having a center axis in common with the center axis of the cylindrical magnet and having an inner circumference larger than an outer circumference of the cylindrical magnet; a plurality of magnetoelectric transducers disposed in a plane transverse to the common center axes of the cylindrical and annular magnets, wherein: the cylindrical magnet and the annular magnet are disposed so that respective, identical magnetic poles thereof are in opposing relationship, and the annular magnet is tiltable with respect to the cylindrical magnet and the plane of the magnetoelectric transducers, and the magnetoelectric transducers detect a change in a magnetic field caused by tilting of the annular magnet relatively to the cylindrical magnet and the plane of the magnetoelectric transducers, so as to input two-dimensional coordinate values according to the detected change in the magnetic field.

The initialed copy of the IDS has been attached with the communications.

BIPIN SHALWALA
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600